4 All rights reserved by Euro Cold S.r.I Modena (Italy). These drawings and specifications are the property of Euro Cold S.r.I. and shall not be reproduced, copied or used directly or undirectly for any purpose without the express written permission of EURO COLD S.r.I TECHNICAL DATA ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE AND OVERALL DIMENSION CAN CHANGE DUE TO THE REQUESTED ACCESSORIES. FRAME AWEX 16S 2 RIVELOX M6 E 250 135 WATER OUT WATER IN 3+3 RIVELOX M6 **LEVEL POWER** 989 650  $\mathbb{D}$ 2 RIVELOX M6 125 125 12 26 FAN PUMP 97 35 240 310 C D. **NLET AIR FILLING** HYDRAULIC CONNECTION SIZES **OUTLET AIR** AWEX 16 S В G.1/4" IN **OUT** G.1/4" Thickness: Material: Z | Y | X | W | V | U | T | S | R | Q | P | O | N | M | L | K | J | I | H | G | F | E | D | C | B | A **EDITION** Scale: Designed: **EURO COLD srl** Date: 06-09-2018 Tel. +39.059.817.8138 www.eurocold.it Sign: Title: Weight (g) Model number: Q.ty: Drawing number: Code: AWEX 16S REV03